			Contract	•			***	
GeM Generalization Azadi Kn Amrit Mahotsav	5T-G-1	199/202	2 - 23	> (olt.	Contract No: GEMC-51168: Generated Date: 24-jun-20 Bid/RA/PR No:GEM/2022/B/	722	
Organisation Details Yel: Central Autonomous Ministry: Ministry of Health and Family Well-	Z. 0-0	6/20-21	Suyer Details	<u> </u>				
Regardment: Department of Health and Family V Regardsation Name: North Eastern Indias Gandal Region	Malfara	/	Email ID:		Stores and Proc 0364-2539032-3 herendra.dever	143		
Mile Zone: Neigrihms, Shillong.	is activity to hearth ship Medical S	ciences (NEIGRIHMS)	GSTIN: Address:		n P.O. NEIGRUMMS,	Mawdiangdiong, Shillong.		
inancial Approval Detail		· · · · · · · · · · · · · · · · · · ·	Davidson Author			S, MEGHALAYA-793018, India		
D Concurrence: Yes esignation of Administrative Approval: Direc esignation of Financial Approval: Depo	ctor NEIGRIHMS Shillong and Head	of Office	Paying Author Payment Mode: Designation:	nty Dec	Offline			
Dept.	uty Director (Admn) and ODO - undo	er Grant in Asset	Emelf ID: GSTIN:		A Accounts office accounts, naigrifu N			
Concevace.	<u> </u>	121-13/	Address:		P.O. NEIGRIHMS, KHASI HILLE EAS	Mawdiangdiang, Shillong, T. MEGHALAYA-783018, India		
eter Details		3/6/12						
14 Seller ID: Impany Name:	156D1800000 MEDEX NOIA	197644 PRIVATE LIMITED						
intect No.:	09811145565 medexindia@	grief,com						
dress: Me verified:	DD 36,KALKAJ NEW DELHI, D Yes	I, ELNI-110019, -						
Më Registration number: Æ Social Category: Æ Gendor:	DL09D000464 General	a						
nii:	Male 07AAACH9017	E1ZP, 07AAACM9017E1ZP, 07AAACI	49017E1ZP					
ST / Tax invoice to be raised in the na	me of - Consignee		-					
oduct Details			T					
Ite	m Description		Ordered Quantity	Unit	Unit Price (IMR)	Tax Bifurcation	(INR)	Price (inclusive of all
Product Mame: RENOSEM 101 to 140 liters Rectangular Brand: RENOSEM	Low temperature Hydrogen Peroxi	de Gas Steriliser			.,	 		Duties and Taxe in INR)
Irrand Type : Registered Brand Calaifogue Status : GEM verified catalogue Leiling As : OEM		:				GST (18%): 1,062,610,169 GST Case 1 (0%): 0		
stegory Name & Quadrant : Low temperature Hydrogen ENO 5-130	Peroxide Gas Steriliser (Q2)		2	bieces	3,483,000	GST Cass 2 (0 per accounting of Imput Tax Credit (ITC) on GS ITC on GST Cass 1: -	unit) : 0 iT: •	6,946,989
Sh not specified by soller Order Value (in INR)						ITC on GST Cose 2: x		
								6,344,000
nsignee Detail					······································			
Designation: -	Item				Lot No. Quantit	y Delivery Start After	Delivery To 8	le (completed By
Email iD: con18.neigrihms.mi@gembuyer.in Contact: 0364-2938044- IGSTIN: -	RENOSEM 101 to 146 from to	stangular Low temperature Hydrogen						
Address: P.O. NEIGRIHMS, Mawdlengdieng, Shillong, EAST KHASI HILLS, MEGHALAYA-793018, India	THE COLUMN TO SERVICE THE PARTY OF THE PARTY	sraußeren rom ressibetarrie iskeloßet.				1 1		
					. 2	24-Jun-2022	22-Sep-2022	
duct Specification for RENOSEM 101 to	140 liters Rectangular L	ow temperature Hydrogel				24-jun-2022	22-Sep-2022	-
fuct Specification for RENOSEM 101 to Ification Sub-Spec	140 Hters Rectangular L	ow temperature Hydrogei Value Low temperature Hydrogen Peroxid	n Peroxide Gas	Sterilis	e la van de la v			w temperature
Usege:		Ow temperature Hydrogei Value Low temperature Hydrogen Peroxide Hydrogen Peroxide gas Steriliser is device surfaces, with cycle time les	n Peroxide Gas	Sterilis	ut low temperature steril	tration process to stariffse heat-ser	nsitive devices, Lo	w temperature d strillsing exposed
Historian Sub-Spec Usege: Type of Hydragen Peroxiste Gas Sterilisation Steriliser is environment friendly and have n	· Technology, used:	Ow temperature Hydrogei Value Low temperature Hydrogen Peroxide Hydrogen Peroxide gas Steriliser is device surfaces, with cycle time les Plasma technology	n Peroxide Gas	Sterilis	ut low temperature steril	tration process to stariffse heat-ser	nsitive devices, Lo	w temperature d sturilising exposed
Usage: Type of Hydragen Perusiste Gas Sterillisation	· Technology, used:	OW temperature Hydrogen Value Low temperature Hydrogen Peroxic Hydrogen Peroxide gas Steriliser is device surfaces, with cycle time less Pleams technology Yes	n Peroxide Gas	Sterilis	ut low temperature steril	tration process to stariffse heat-ser	nsitive devices, Lo	w temperature d strillsing exposed
Usege: Type of Hydragen Peroxiste Gas Sterilisation Steriliser is environment friendly and have n readduals: Shape of Sterilisation Chamber: Usable space (usable capacity) of Sterilization	Technology used: to task by products or harmful	Ow temperature Hydrogei Value Low temperature Hydrogen Peroxide Hydrogen Peroxide gas Steriliser is device surfaces, with cycle time les Plasma technology	n Peroxide Gas	Sterilis	ut low temperature steril	tration process to stariffse heat-ser	nsitive devices, Lo	w temperature d sturilising exposed
Usege: Type of Hydragen Peroxiste Gas Sterilisation Steriliser is environment friendly and have in residuals: Shape of Sterilisation Chamber:	Technology used: to task by products or harmful	Ow temperature Hydrogen Value Low temperature Hydrogen Peroxic Hydrogen Peroxide gas Steriliser is device surfaces, with cycle time less Pleama technology Yes Rectangular 101 to 140 liters Pheumatically or electrically control	n Peroxide Ges	Steriiis carrying o temperatur steriisation	ut low temperature sterile ste	tration process to sterifise heat-ser 2 vapour filling the sterifiser chamb uitable for sterifising heat-sensitive	nsitive devices. Lo ner, contacting and devices.	w temperature distrillsing exposed
Usege: Type of Hydragen Peroxiste Gas Sterilisation Steriliser is environment friendly and have in readdusis: Shape of Sterilisation Chember: Useble space (useble capacity) of Sterilization Sterilisation Chember Door: Control System: Sterilisation Monitoring and Alerms:	Technology used: no toxic by products or hermful on Chember fells with in the range:	Ow temperature Hydrogen Value Low temperature Hydrogen Peroxic Hydrogen Peroxide gas Steriliser is device surfaces, with cycle time less Pleama technology Vet Rectangular 101 to 140 liters Pheumatically or electrically control Microprocessor controlled system with the control of the c	n Peroxide Gas se gas Sterifizer is for for carrying out low it ser than alternative : ser than alternative : sed door with comple th clear user interfac	carrying o carrying o temperatur sterilisation	ut low temperature sterile ste	tration process to sterifise heat-ser 2 vapour filing the sterifiser chambuiltable for sterifising heat-sensitive uitable for sterifising heat-sensitive	nsitive devices. Lo ner, contacting and devices.	d strillsing exposed
Usege: Type of Hydragen Peroxiste Gas Sterilisation Steriliser is environment friendly and have in readduals: Shape of Sterilisation Chamber: Usable space (usable capacity) of Sterilization Sterilisation Chamber Door: Control System:	Technology used: no toxic by products or hermful on Chember fells with in the range:	Justice Low temperature Hydrogen Peroxic Hydrogen Peroxide gas Steriliser is device surfaces, with cycle time less Pleama technology Yes Rectangular 101 to 140 liters Phearmatically or electrically control Microprocessor controlled systems with Steriliser has facility to completely research and smart information technology.	n Peroxide Gas se gas Sterifizer is for for carrying out low it ser than alternative s sed door with comple th clear user interfac nonitor its operations by device for automs	carrying o carrying o carrying o carrying or carrying	ut low temperature sterile ste	tration process to sterifise heat-ser 2 vapour filing the sterifiser chambuiltable for sterifising heat-sensitive uitable for sterifising heat-sensitive day.	nsitive devices. Lo ner, contacting and devices.	d strillsing exposed
Usege: Type of Hydragen Perusids Gas Sterilisation Seriliser is environment friendly and have n readcusts: Shepe of Sterilisation Chember: Useble space (usable capacity) of Sterilisatio Sterilisation Chember Door: Control System: Sterilisation Monitoring and Alerms: Built in facility for recording and printing cycl	Technology used: no toxic by products or hermful on Chember fells with in the range:	OW temperature Hydrogen Peroxic Hydrogen Peroxide gas Steriliser is device surfaces, with cycle time less Pleama technology Yes Rectangular 103 to 140 liters Pheumatically or electrically control Microprocessor controlled system w Steriliser has facility to completely in	n Peroxide Gas se gas Sterifizer is for for carrying out low it ser than alternative s sed door with comple th clear user interfac nonitor its operations by device for automs	carrying o carrying o carrying o carrying or carrying	ut low temperature sterile ste	tration process to sterifise heat-ser 2 vapour filing the sterifiser chambuiltable for sterifising heat-sensitive uitable for sterifising heat-sensitive day.	nsitive devices. Lo ner, contacting and devices.	d strillsing exposed
Hearties Sub-Spec Usege: Type of Hydrogen Peroxide Gas Sterilisation Sterilise is environment friendly and have n residuals: Shape of Sterilisation Chamber: Useble space (usable capacity) of Sterilisatio Sterilisation Chamber Door: Control System: Sterilisation Monitoring and Alarms: Built in facility for recording and printing cycl Mobility: Cycle temperature range: Have pre-geogrammed sterilisation cycles for	Technology used: To toxic by products or hermful To toxic by pro	Ow temperature Hydrogen Peroxic Hydrogen Peroxic Hydrogen Peroxic gas Steriliser is device surfaces, with cycle time less Pearast technology Ves Rectangular 103 to 40 liters Phaumatically or electrically control Microprocessor controlled system we Steriliser has facility to completely rives and smart information technology.	n Peroxide Gas se gas Sterifizer is for for carrying out low it ser than alternative s sed door with comple th clear user interfac nonitor its operations by device for automs	carrying o carrying o carrying o carrying or carrying	ut low temperature sterile ste	tration process to sterifise heat-ser 2 vapour filing the sterifiser chambuiltable for sterifising heat-sensitive uitable for sterifising heat-sensitive day.	nsitive devices. Lo ner, contacting and devices.	d strillsing exposed
Usage: Type of Hydragen Peroxiste Gas Sterilisation Sterilisatis is environment friendly and have n realduals: Shape of Starilisation Chamber: Usable space (usable capacity) of Sterilizatio Sterilisation Chamber Door; Control System: Sterilisation Monitoring and Alerms: Built in facility for recording and printing cycl Mobility: Cycle temperature range: Have pre acogrammed starilisation cycles for and flexible larms: Built ion@listy features available:	Technology used: to toxic by products or harmful on Chember fells with in the range; le details:	Ow temperature Hydrogen Value Low temperature Hydrogen Peroxic hydrogen Peroxide gas Steriliser is device surfaces, with cycle time les device surfaces, with cycle time les Pleama technology Yes Rectangular 101 to 140 liters Pneumatically or electrically control Microprocessor controlled system w Steriliser has facility to completely r Yes and smart information technology Mobile on castor wheel and compact 35 degree to 60 degree cartigrade.	n Peroxide Ges fe ges Steffizer is for carrying out low it ser than alternative : fed door with comple th clear user interfac nonitor its operations only device for automs in design,	Sterijis carying o	ut low temperature steril e sterilisation using HZO forms and it involves. Si respect with multiple lock polymer and display of cycle pr visual aterms and aterms n , reconciliation & come	tration process to sterifise heat-ser 2 vapour filing the sterifiser chambuiltable for sterifising heat-sensitive uitable for sterifising heat-sensitive day.	nsitive devices. Lo ner, contacting and devices.	d strillsing exposed
Usage: Type of Hydragen Peroxiste Gas Sterilisation Sterilisat is environment friendly and have n residuals: Shape of Sterilisation Chamber: Usable space (usable capacity) of Sterilizatio Sterilisation Chamber Door: Control System: Sterilisation Monitoring and Alarms: Built indicate the first for recording and printing cycl Mobility: Cycle tamperature range: Have are grogrammed sterilisation cycles for and fleetible items: Built isegisty restures available: Have an easy to troubleshoot by display intervalable from the front:	Technology used: To toxic by products or hermful The toxic by products o	Ow temperature Hydrogen Peroxic Value Los temperature Hydrogen Peroxide Hydrogen Peroxide gas Steriliser is device surfaces. with cycle time les Plasma technology Yes Rectangular 101 to 140 liters Pneumatically or electrically control Microprocessor controlled system us Steriliser has facility to completely r Yes and smart information technolog Mobile on castor wheel and compact 35 degree to 60 degree centigrade.	n Peroxide Ges fe ges Steffizer is for carrying out low it ser than alternative : fed door with comple th clear user interfac nonitor its operations only device for automs in design,	Sterijis carying o	ut low temperature steril e sterilisation using HZO forms and it involves. Si respect with multiple lock polymer and display of cycle pr visual aterms and aterms n , reconciliation & come	tration process to sterifise heat-ser 2 vapour filing the sterifiser chambuiltable for sterifising heat-sensitive uitable for sterifising heat-sensitive day.	nsitive devices. Lo ner, contacting and devices.	d strillsing exposed
Usage: Type of Hydrogen Peroxiste Gas Sterilisation Steriliser is environment friendly and have in realiduals: Shape of Sterilisation Chamber. Usable space (usable capacity) of Sterilisation Scerilisation Chamber Door; Control System: Sterilisation Monitoring and Alarms: Built in facility for recording and printing cycl Mobility. Cycle temperature range: Have are accognammed sterilisation cycles for and fleasible Barns: Built inegality returns available: Have an easy to troubleshoot by display interavailable from the front: Interface for remote supervision and date sto	Technology used: To toxic by products or hermful The toxic by products o	Ow temperature Hydrogen Peroxic Low temperature Hydrogen Peroxic Low temperature Hydrogen Peroxic Hydrogen Peroxide gas Sterilisar is device surfaces, with cycle time les device surfaces, with cycle time les Plasma technology Yes Rectangular 101 to 140 liters Pneumatically or electrically control Microprocesor controlled system w Steriliser has facility to completely r Yes and smart information technolog Mobile on castor wheel and compact 15 degree to 60 degree centigrade, Yes Emergency stop, Door safety, Over It	In Peroxide Ges In gas Sterifizer is for for carrying out low it see than alternative; ind door with comple ind door with comple ind clear user interfa- monitor in the for automa in design.	Sterijis carying o	ut low temperature steril e sterilisation using HZO forms and it involves. Si respect with multiple lock polymer and display of cycle pr visual aterms and aterms n , reconciliation & come	tration process to sterifise heat-ser 2 vapour filing the sterifiser chambuiltable for sterifising heat-sensitive uitable for sterifising heat-sensitive day.	nsitive devices. Lo ner, contacting and devices.	d strillsing exposed
Usage: Type of Hydrogen Peroxiste Gas Sterilisation Steriliser is environment triendly and have n readduals: Shape of Sterilisation Chamber Usable space (usable capacity) of Sterilizatio Sterilisation Chember Door: Control System: Sterilisation Monitoring and Alerms: Built in facility for recording and printing cycl Mobility: Cycle temperature range: Have pre programmed sterilisation cycles for and flesible laums: Built insgilliby freatures available: Have an easy to troubleshoot by display intervaliable from the front: Interface for remote supervision and data stor If Process certificate ENISO 14937 available: Certification for sterilization of metal and non	Technology used: to toxic by products or harmful on Chamber falls with in the range: the details: flat instruments and for hollow face and all services access rage: metail instruments:	Ow temperature Hydrogen Peroxic Low temperature Hydrogen Peroxic Hydrogen Peroxide gas Sterilisar is device surfaces, with cycle time les device surfaces, with cycle time les Plasma technology Yes Rectangular 101 to 140 liters Pneumatically or electrically control Microprocesor controlled system w Steriliser has facility to completely r Yes and smart information technolog Mobile on castor wheel and compact 15 degree to 60 degree centigrade. Yes Emergency stop, Door safety, Over It	In Peroxide Ges In gas Sterifizer is for for carrying out low it see than alternative; ind door with comple ind door with comple ind clear user interfa- monitor in the for automa in design.	Sterijis carying o	ut low temperature steril e sterilisation using HZO forms and it involves. Si respect with multiple lock polymer and display of cycle pr visual aterms and aterms n , reconciliation & come	tration process to sterifise heat-ser 2 vapour filing the sterifiser chambuiltable for sterifising heat-sensitive uitable for sterifising heat-sensitive day.	nsitive devices. Lo ner, contacting and devices.	d sit rillsing exposed
Usage: Type of Hydrogen Peroxiste Gas Starillisation Stariliser is environment friendly and have in realiduals: Shape of Starillisation Chamber: Usable space (usable capacity) of Starillisation Starilisation Chamber Door; Control System: Starilisation Monitoring and Alarms: Built in facility for recording and printing cycl Mobility; Cycle temperature range: Have are accorammed starilisation cycles for and fleatible Burns: Built infacility features available: Have an easy to troubleshoot by display interavailable from the front: Interface for remote supervision and date stol if Process certificate ENISO 14937 available:	Technology used: to toxic by products or harmful on Chamber falls with in the range: the details: flat instruments and for hollow face and all services access rage: metail instruments:	Ow temperature Hydrogen Peroxic Low temperature Hydrogen Peroxic Hydrogen Peroxide gas Sterilisar is device surfaces, with cycle time les device surfaces, with cycle time les Plasma technology Yes Rectangular 101 to 140 liters Pmeumatically or electrically control Microprocesor controlled system w Sterilisar has facility to completely r Yes and smart information technolog Mobile on castor wheel and compact 15 degree to 60 degree centigrade, Yes Emergency stop, Door safety, Over It Yes	In Peroxide Ges In gas Sterifizer is for for carrying out low it see than alternative; ind door with comple ind door with comple ind clear user interfa- monitor in the for automa in design.	Sterijis carying o	ut low temperature steril e sterilisation using HZO forms and it involves. Si respect with multiple lock polymer and display of cycle pr visual aterms and aterms n , reconciliation & come	tration process to sterifise heat-ser 2 vapour filing the sterifiser chambuiltable for sterifising heat-sensitive uitable for sterifising heat-sensitive day.	nsitive devices. Lo ner, contacting and devices.	d sit rillsing exposed
Jisege: Type of Hydragen Peroxiste Gas Sterilisation Sterifiser is environment friendly and have in redducials: Shape of Sterilisation Chamber: Usable space (usable capacity) of Sterilisation Scerilisation Chamber Door: Control System: Sterilisation Monitoring and Alarms: Built in facility for recording and printing cycl Mobility: Cycle tamperature range: Have are strogrammed sterilisation cycles for and flexible Bams: Built ineglish; returns available: Have an easy to troubleshoot by display inter available from the front: Interface for remote supervision and date sto if Process certificate ENISO 14937 available: Certification for sterilization of metal and non Censumables be supplied with each Sterilisation Sterilisation cycles(at least): Warranty (Option of comprehensive werranty.	Technology used: Technology used: To taxic by products or harmful The control of the control	United Low temperature Hydrogen Peroxic United States Control of the Management of t	In Peroxide Ges In gas Sterifizer is for for carrying out low it see than alternative; ind door with comple ind door with comple ind clear user interfa- monitor in the for automa in design.	Sterijis carying o	ut low temperature steril e sterilisation using HZO forms and it involves. Si respect with multiple lock polymer and display of cycle pr visual aterms and aterms n , reconciliation & come	tration process to sterifise heat-ser 2 vapour filing the sterifiser chambuiltable for sterifising heat-sensitive uitable for sterifising heat-sensitive day.	nsitive devices. Lo ner, contacting and devices.	d sit rillsing exposed
Usage: Type of Hydrogen Peroxide Gas Sterilisation Steriliser is environment friendly and have n realduals: Shape of Sterilisation Chamber: Usable space (usable capacity) of Sterilizatio Sterilisation Chamber Door: Control System: Sterilisation Monitoring and Alarms: Built in facility for recording and printing cycl Mobility: Cycle temperature range: Have pre-programmed sterilisation cycles for and fleesible Burns: Built in facility features available: Have an easy to troubleshoot by display inter- available from the front: Interface for remote supervision and data sto- if Process certificate ENISO 14937 available: Certification for sterilization of metal and non Censumables be supplied with each sterilization cellisation cycles(at least): Warranty (Option of comprehensive warranty, which if opted will supersade normal warranty	Technology used: In technology used: In technology used: In technology used: In the range: In Chamber falls with in the range: In Chamber falls with in the range: In details: If at instruments and for hollow If are and all services access If are an are an are an are an are are an are	United Low temperature Hydrogen Peroxic United States Control of the Management of t	In Peroxide Ges In gas Sterifizer is for for carrying out low it see than alternative; ind door with comple ind door with comple ind clear user interfa- monitor in the for automa in design.	Sterijis carying o	ut low temperature steril e sterilisation using HZO forms and it involves. Si respect with multiple lock polymer and display of cycle pr visual aterms and aterms n , reconciliation & come	tration process to sterifise heat-ser 2 vapour filing the sterifiser chambuiltable for sterifising heat-sensitive uitable for sterifising heat-sensitive day.	nsitive devices. Lo ner, contacting and devices.	d sit rillsing exposed
Usage: Type of Hydrogen Peroxide Gas Sterilisation Searliser is environment friendly and have n residuals: Shape of Sterilisation Chamber: Usable space (usable capacity) of Sterilisation Sterilisation Chamber Door: Control System: Sterilisation Monitoring and Alarms: Built in facility for recording and printing cycl Mobility: Cycle temperature range: Have pre geogrammed sterilisation cycles for and fleesible Burns: Built inegalist restures aveilable: Have an easy to troubleshoot by display inter- aveilable from the front: Interface for remote supervision and data sto If Process certificate ENISO 14937 available: Certification for sterilization of metal and non Censumables be supplied with each 3terilisation Certification for sterilization of metal and non Censumables be supplied with each 3terilisation Warranty (Option of comprehensive werranty, which if opted will supersade normal warranty Sterilizing Chamber has sufficient dimensions units:	Technology used: to toxic by products or harmful on Chember fells with in the range: on Chember fells with in the range: le details: rise instruments and for hollow face and all services access rage: metal instruments: on Unit sufficient for nunning full is available through bidding only, in the catalogue) imperature: for sterikaing rigid telescope	United Low temperature Hydrogen Peroxic United States of the Indiana Control of the Indiana	In Peroxide Ges In gas Sterifizer is for for carrying out low it see than alternative; ind door with comple ind door with comple ind clear user interfa- monitor in the for automa in design.	Sterijis carying o	ut low temperature steril e sterilisation using HZO forms and it involves. Si respect with multiple lock polymer and display of cycle pr visual aterms and aterms n , reconciliation & come	tration process to sterifise heat-ser 2 vapour filing the sterifiser chambuiltable for sterifising heat-sensitive uitable for sterifising heat-sensitive day.	nsitive devices. Lo ner, contacting and devices.	d sit rillsing exposed
Usage: Type of Hydrogen Peroxide Gas Sterilisation Steriliser is environment friendly and have n realduals: Shape of Sterilisation Chamber: Usable space (usable capacity) of Sterilisation Sterilisation Chamber Door: Control System: Sterilisation Monitoring and Alarms: Built in facility for recording and printing cycl Mobility: Cycle temperature range: Have pre programmed sterilisation cycles for and fleesible Berns: Built inegitally restures aveilable: Have an easy to troubleshoot by display inter- available from the front: Interface for remote supervision and data sto- if Process certificate ENISO 14937 available: Certification for sterilization of metal and non Canaumatics be supplied with each Sterilisation Sterilisation cycles(e) least): Warranty (Option of comprehensive werranty, which if opted will supersade normal warranty Sterilising Chamber has sufficient dimensions units: Sterilizare unit have been recommended by at it manufacturers (details to be given by Seler to	Technology used: to toxic by products or harmful on Chamber falls with in the range: on Chamber falls with in the range; file details: If at instruments and for hollow face and all services access rage: metal instruments: on Unit sufficient for running full is available through bidding only, in the catalogue) imperature: for sterikizing rigid telescope least three medical device lawyer on demand the startilizer	Jobs temperature Hydrogen Peroxide Low temperature Hydrogen Peroxide Low temperature Hydrogen Peroxide Hydrogen Peroxide gas Storiliser is device surfaces, with cycle time les Plearma technology Yes Rectangular 103 to 140 liters Pneumatically or electrically control Microprocessor controlled system w Sterifiser has facility to completely r Yes and smart information technolog Mobile on castor wheel and compact 35 degree to 60 degree centigrade, Yes Emergency stop, Door safety, Over h Yes European CE 200 5 Yes	In Peroxide Ges In gas Sterifizer is for for carrying out low it see than alternative; ind door with comple ind door with comple ind clear user interfa- monitor in the for automa in design.	Sterijis carying o	ut low temperature steril e sterilisation using HZO forms and it involves. Si respect with multiple lock polymer and display of cycle pr visual aterms and aterms n , reconciliation & come	tration process to sterifise heat-ser 2 vapour filing the sterifiser chambuiltable for sterifising heat-sensitive uitable for sterifising heat-sensitive day.	nsitive devices. Lo ner, contacting and devices.	d strillsing exposed
Usage: Type of Hydrogen Peroxide Gas Sterilisation Searliser is environment friendly and have n residuals: Shape of Sterilisation Chamber: Usable space (usable capacity) of Sterilisation Sterilisation Chamber Door: Control System: Sterilisation Monitoring and Alarms: Built in facility for recording and printing cycl Mobility: Cycle temperature range: Have pre geogrammed sterilisation cycles for and fleesible Burns: Built inegalist restures aveilable: Have an easy to troubleshoot by display inter- aveilable from the front: Interface for remote supervision and data sto If Process certificate ENISO 14937 available: Certification for sterilization of metal and non Censumables be supplied with each 3terilisation Certification for sterilization of metal and non Censumables be supplied with each 3terilisation Warranty (Option of comprehensive werranty, which if opted will supersade normal warranty Sterilizing Chamber has sufficient dimensions units:	Technology used: to toxic by products or harmful on Chamber falls with in the range: on Chamber falls with in the range; file details: If at instruments and for hollow face and all services access rage: metal instruments: on Unit sufficient for running full is available through bidding only, in the catalogue) imperature: for sterikizing rigid telescope least three medical device lawyer on demand the startilizer	Jobs temperature Hydrogen Peroxide Low temperature Hydrogen Peroxide Low temperature Hydrogen Peroxide Hydrogen Peroxide gas Storiliser is device surfaces, with cycle time les Plearma technology Yes Rectangular 103 to 140 liters Pneumatically or electrically control Microprocessor controlled system w Sterifiser has facility to completely r Yes and smart information technolog Mobile on castor wheel and compact 35 degree to 60 degree centigrade, Yes Emergency stop, Door safety, Over h Yes European CE 200 5 Yes	In Peroxide Ges In gas Sterifizer is for for carrying out low it see than alternative; ind door with comple ind door with comple ind clear user interfa- monitor in the for automa in design.	Sterijis carying o	ut low temperature steril e sterilisation using HZO forms and it involves. Si respect with multiple lock polymer and display of cycle pr visual aterms and aterms n , reconciliation & come	tration process to sterifise heat-ser 2 vapour filing the sterifiser chambuiltable for sterifising heat-sensitive uitable for sterifising heat-sensitive day.	nsitive devices. Lo ner, contacting and devices.	d sit rillsing exposed
Usage: Type of Hydrigen Peroxide Gas Sterilisation Steriliser is environment friendly and have in realduals: Shape of Sterilisation Chamber: Usable space (usable capacity) of Sterilizatio Sterilisation Chamber Door: Control System: Sterilisation Monitoring and Alarms: Built in facility for recording and printing cycl Mobility: Cycle temperature range: Have pre programmed sterilisation cycles for and fleesible Berns: Built inegalish restures available: Have an easy to troubleshoot by display inter available from the front: Interface for remote supervision and date sto If Process certificate ENISO 14937 available: Certification for sterilization of metal and non Consumables be supplied with seen Sterilization Sterilization cycles(e) leads): Werranty (Option of comprehensive werranty which if opted will supersade normal warranty Sterilizing Chamber has sufficient dimensions units: Sterilizate units suitable to be stored at room to Sterilizate units suitable to be stored at room to Sterilizate units devices of their make such as telescop medical devices of their make such as telescop	Technology used: to toxic by products or harmful to toxic by products or harmful on Chamber falls with in the range: flet details: flet instruments and for hollow face and all services access rage: metal instruments: on Unit sufficient for running fulf is available through bidding only, in the catalogue) amparature: for sterikting rigid telescope least three medical device lesst three medical device less three medical device	United Low temperature Hydrogen Peroxide Low temperature Hydrogen Peroxide gas Starilisar is device surfaces. with cycle time less Pleama technology Yes Rectangular 101 to 140 liters Presumatically or electrically control Microprocessor controlled system we Starilisar has facility to completely ryes and smart information etchnology Mobile on ceator wheel and compact Starilisar has facility to completely ryes and smart information technology Mobile on ceator wheel and compact Starilisar has facility to completely ryes. Emergency stop, Door safety, Over hyes Yes Emergency stop, Door safety, Over hyes Yes European CE 200 5	n Peroxide Ges ie gas Sterilizer is for for carrying out low it ser than alternative : led door with comple the clear user interface nonitor its operations by device for automa in design. Death protection, Electron on and data storage.	Sterilis carrying a carrying a carrying to the safety territable of	ut low temperature sterils at sterilisation using HZO forms and it involves. Si record with multiple lock of and display of cycle provisual aterms and alarm in reconciliation 6 comments.	tration process to sterifise heat-ser 2 vapour filing the sterifiser chambuiltable for sterifising heat-sensitive uitable for sterifising heat-sensitive day.	nsitive devices. Lo ner, contacting and devices.	d strillsing exposed
Usage: Type of Hydrogen Peroxide Gas Sterilisation Steriliser is environment friendly and have n realduals: Shape of Sterilisation Chamber: Usable space (usable capacity) of Sterilisation Sterilisation Chamber Door: Control System: Sterilisation Monitoring and Alarms: Built in facility for recording and printing cycl Mobility: Cycle temperature range: Have pre programmed sterilisation cycles for and fleesible Berns: Built inegitally restures aveilable: Have an easy to troubleshoot by display inter- aveilable from the front: Interface for remote supervision and data sto- if Process certificate ENISO 14937 available: Certification for sterilization of metal and non Canaumaties be supplied with each Sterilisation Sterilisation cycles(e) least): Warranty (Option of comprehensive werranty, which if opted will supersade normal warranty Sterilizing Chamber has sufficient dimensions units: Sterilizar units suitable to be stored at room to Sterilizar units suitable to be stored at room to Sterilizar units suitable to be stored at room to Sterilizar units suitable to be stored at room to Sterilizar units suitable to be stored at room to Sterilizar units suitable to be stored at room to Sterilizar units suitable to be stored at room to Sterilizar units suitable to be stored at room to sterilizar units suitable to be stored at room to sterilizar units suitable to be stored at room to sterilizar units suitable to be stored at room to sterilizar units suitable to be stored at room to sterilizar units suitable to be stored at room to sterilizar units suitable to be stored at room to sterilizar units suitable to be stored at room to sterilizar units suitable to be stored at room to sterilizar units suitable to be stored at room to sterilizar units suitable to be stored at room to sterilizar units suitable to be stored at room to sterilizar units suitable to be stored at room to sterilizar units suitable to be stored at room to sterilizary units have been recommended by at it manufacturers (datable to be stored at room to	Technology used: to toxic by products or harmful on Chamber falls with in the range: on Chamber falls with in the range: le details: flat instruments and for hollow face and all services access rage: metal instruments: on Unit sufficient for running full is available through bidding only, in the catalogue) imparature: for sterilizing rigid talescope least three medical device surger or sterilizing ones, camera head etc NOSEM 101 to 140 litters rvice Year	United Low temperature Hydrogen Peroxide Low temperature Hydrogen Peroxide gas Starilisar is device surfaces. with cycle time less Pleama technology Yes Rectangular 101 to 140 liters Presumatically or electrically control Microprocessor controlled system we Starilisar has facility to completely ryes and smart information etchnology Mobile on ceator wheel and compact Starilisar has facility to completely ryes and smart information technology Mobile on ceator wheel and compact Starilisar has facility to completely ryes. Emergency stop, Door safety, Over hyes Yes Emergency stop, Door safety, Over hyes Yes European CE 200 5	n Peroxide Ges ie gas Sterilizer is for for carrying out low it ser than alternative : led door with comple the clear user interface nonitor its operations by device for automa in design. Death protection, Electron on and data storage.	Sterilis carrying a carrying a carrying to the safety territable of	ut low temperature sterils at sterilisation using HZO forms and it involves. Si record with multiple lock of and display of cycle provisual aterms and alarm in reconciliation 6 comments.	tration process to sterifise heat-ser 2 vapour filing the sterifiser chambuiltable for sterifising heat-sensitive uitable for sterifising heat-sensitive day.	messages. h 30 minutes read	d strillsing exposed
Usage: Type of Hydrogen Peroxiste Gas Sterilisation Sterifiser is environment friendly and have in reliduals: Shape of Sterilisation Chamber: Usable space (usable capacity) of Sterilisation Sterilisation Chamber Door: Control System: Sterilisation Monitoring and Alarms: Built in facility for recording and printing cycl Mobility: Cycle temperature range: Have pre programmed sterilisation cycles for and flexible Barns: Built is equilible from the front: wherface for remote supervision and date sto if Process certificate ENISO 14937 available: Certification for sterilization of metal and non Censumables be supplied with each Sterilisation Sterilisation cycles(at least): Warranty (Option of comprehensive werranty, which if opted will supersade normal warranty Sterilizary Chamber has sufficient dimensions units: Sterilizary unit have been recommended by at i manufacturers (datalis to be given by Seiter to medical devices of their make such as talesco	Technology used: to toxic by products or harmful on Chember falls with in the range: in Chember falls with in the range: in Chember falls with in the range: ile details: if let instruments and for hollow face and all services access rage: metal instruments: on Unit sufficient for running full is available through bidding only, in the catalogue) imperature: for sterilizing rigid telescope sest three medical device istyrer on demand) for sterilizing ses, camera head etc NOSEM 101 to 140 litters rvice Year ilpment	United Low temperature Hydrogen Peroxide Low temperature Hydrogen Peroxide gas Starilisar is device surfaces. with cycle time less Pleama technology Yes Rectangular 101 to 140 liters Presumatically or electrically control Microprocessor controlled system we Starilisar has facility to completely ryes and smart information etchnology Mobile on ceator wheel and compact Starilisar has facility to completely ryes and smart information technology Mobile on ceator wheel and compact Starilisar has facility to completely ryes. Emergency stop, Door safety, Over hyes Yes Emergency stop, Door safety, Over hyes Yes European CE 200 5	n Peroxide Ges ie gas Sterilizer is for for carrying out low it ser than alternative : led door with comple the clear user interface nonitor its operations by device for automa in design. Death protection, Electron on and data storage.	Sterilis carrying a carrying a carrying to the safety territable of	ut low temperature sterils at sterilisation using HZO forms and it involves. Si record with multiple lock of and display of cycle provisual aterms and alarm in reconciliation 6 comments.	tration process to starifise heat-sen 2 vapour filling the starifiser chambitrable for starifishing heat-sensitive indicates the starifishing heat-sensitive and the starifishing heat-sensitive ding. Indicate the starifishing heat-sensitive and t	messages. h 30 minutes read	d strillsing exposed
Usege: Type of Hydragen Peroxiste Gas Sterilisation Steriliser is environment friendly and have a readuals: Shape of Starilisation Chamber: Usable space (usable capacity) of Sterilisatio Sterilisation Chamber Door: Control System: Sterilisation Monitoring and Alerms: Built in facility for recording and printing cycl Nobility: Cycle temperature range: Have pre programmed sterilisation cycles for and flexible lams: Built in facility features available: Have an easy to troubleshoot by display interessable from the front: Interface for remote supervision and data stor If Process certificate ENISO 14937 available: Certification for sterilization of metal and non Consumables be supplied with each Sterilisational Sterilisation cycles(a) leash: Warranty (Option of comprehensive werranty, which if opted will supersade normal warranty Sterilizing Chember has sufficient dimensions units: Sterilizor unit have been recommended by at inamurfacturers (details to be given by Setler to medical devices of their make such as telescop	Technology used: to toxic by products or harmful on Chember falls with in the range: in Chember falls with in the range: in Chember falls with in the range: ile details: if let instruments and for hollow face and all services access rage: metal instruments: on Unit sufficient for running full is available through bidding only, in the catalogue) imperature: for sterilizing rigid telescope sest three medical device istyrer on demand) for sterilizing ses, camera head etc NOSEM 101 to 140 litters rvice Year ilpment	United Low temperature Hydrogen Peroxide Low temperature Hydrogen Peroxide gas Starilisar is device surfaces. with cycle time less Pleama technology Yes Rectangular 101 to 140 liters Presumatically or electrically control Microprocessor controlled system we Starilisar has facility to completely ryes and smart information etchnology Mobile on ceator wheel and compact Starilisar has facility to completely ryes and smart information technology Mobile on ceator wheel and compact Starilisar has facility to completely ryes. Emergency stop, Door safety, Over hyes Yes Emergency stop, Door safety, Over hyes Yes European CE 200 5	n Peroxide Ges ie gas Sterilizer is for for carrying out low it ser than alternative : led door with comple the clear user interface nonitor its operations by device for automa in design. Death protection, Electron on and data storage.	Sterilis carrying a carrying a carrying to the safety territable of	ut low temperature sterils at sterilisation using HZO forms and it involves. Si record with multiple lock of and display of cycle provisual aterms and alarm in reconciliation 6 comments.	tration process to starifise heat-sen 2 vapour filling the starifiser chambitrable for starifishing heat-sensitive indicates the starifishing heat-sensitive and the starifishing heat-sensitive ding. Indicate the starifishing heat-sensitive and t	messages. h 30 minutes read	d sit rillsing exposed

Service Year LMC charges for 3 rd year after warranty period in % or cost of equipment	CMC Percentage	THAT SINGUESATION INput Tax Cradit (ITC) on GST:-
CMC charges for 4 th year after warranty period in % of cost of equipment	3%	ITC on dST Cons 1:-
CMC charges for 5 th year after warranty period in % of cost of equipment	3%	
Buyer Defined Additional Specification for RENOSEM 101 to 140 litera Rectangular Low ter	nperature Hydrogen Peroxide Ges Star	Mear
Specification	Value	
Fully microprocessor controlled with universal data acquisition system using Hydrogen peroxide gas plasma technology free floor standing and mobile on lockable castors	Fully microprocessor controlled with universal data acc standing and mobile on lockable castors	uisition system using Hydrogen peroxide gas plesma technology free floor
Regular and prolonged sterilization cycle time between 45 to 65 minutes 6 fest cycle around 33 minutes . Steriëzation temperature around 55 degrees C	Regular and prolonged sterilization cycle time between around 55 degrees C	45 to 65 minutes & fast cycle around 35 minutes .Steriliza ion temperature
To sterifice all surgical instruments, hollow tubes endoscopes rigid & flexible, flexible tumen inside diemeter 1 & length 2000 & 500 mm (rigid) respectively	To sterikze all surgical instruments, hollow tubes endor mm (rigid) respectively	scopes rigid & flexible, flexible lumen inside diameter 1 & length 2000 & 500
Equipment should be to sterilize instruments of Robotic systems. (Claims backed by certificate from OEM of robotic system to be provided).	Equipment should be to sterilize instruments of Robotic provided).	: systems. (Claims backed by certificate from OEM of roboti: system to be
To offer cost of all consumebles as % of system cost in ATC1/2 & The complete consumable to run at least 100 cycles	To offer cost of all consumables as % of sustam cost in	ATCAR

- 1. Extended Upto : 2022-02-19 14:00:00
 2. Extended Upto : 2022-02-28 14:00:00
 3. Get-Oldring-Corr-3117722-5.pdf cill
 4. Extended Upto : 2022-03-03 16:00:00
 5. Extended Upto : 2022-03-04 18:00:00

dditional Clauses for CMC

LCMC shall include preventive maintenance including calibration as per technical service /aperational manual of the manufacturer's technical/ service charges and spares, after satisfactory completion of Warranty. During the CMC period commencing from data of the successful completion of warranty period. Service personnel shall visit each consignee site as recommended in the manufacturer's technical/ service /aperational manual, at least once in six months or as per user requirement. Cost of consumebles shall not be 2.CMC charges to be indicated as percentage of cost of equipment quoted for each year after the warranty period.

3.GST shall be included in the CMC Charges quoted.

3.GST shall be included in the CMC Charges quoted.

3.The payment of CMC will be added for Ranking/Evaluation purpose with depreciation formula. A 10% discounting rate per year shall be applied on CMC Charges for price evaluation on Net Present Value.

3.The payment of CMC will be made on questrately besis after asstatectory completion of said period, duly certified by end user.

6.White cristing a bid or RA, buyers shall indicate whether CMC is required against Yes/No* options. If CMC Charges are included, an option for number of years for CMC required after the warranty period shall be available. Under this option up to 10 years can be considered to the considerable period.

7.In case the bid has a provision for CMC, the warranty of the product will also be deemed to have been converted into Comprehensive warranty including preventive maintenance and calibration as per technical/ service /operational manual of the minufacture service charges and spares, during the Warranty period also. Sellers are therefore advised to include the cost of Comprehensive warranty including pares (excluding consumables) also in product cost.

a.The CMF (functionality shall be available in hid only and no direct RA shall be applicable. In case of bid to RIA decrement rules shall be applicable on total price inclusive of CMC charges. Bunching of products sha

8.1. Buyer shall indicate number of years of warranty by selecting different options available in the field depending on warranty parameter applicable in category parameters for the equipment. No. of years of warranty indicated here shall supersede the warranty period indicated elsewhere in bid or product specifications. The Select while participating in Bid/RA will get fields to indicate CMC charges as percentage depending on number of years of CMC selected by Buyer. The following shall be applicable, if

Syear CMC selected:

CMC charges for 1st year after warranty period - Percentage to be indicated - A1

CMC charges for 2nd year after warranty period - Percentage to be indicated - A2

CMC charges for 3rd year after warranty period - Percentage to be indicated - A2

CMC charges for 4h year after warranty period - Percentage to be indicated - A3

CMC charges for 4h year after warranty period - Percentage to be indicated - A4

CMC charges for 5th year after warranty period - Percentage to be indicated - A5

Similarly, As to A10 are to be indicated for 5th to 10th year of CMC if applicable.

82.The celculation of CMC charges after warranty period - Percentage to be indicated - A5

83.3.In the price evaluation, the system shall take into account the number of years of warranty and duration of CMC as specified while creating bid.

83.3.In the price evaluation, the system shall provide function to esiculate the cost of each equipment by formula indicated below includingCMC and then show the inter-se-ranking of the bidders. The following are the variet (ii) Number of years for product warranty

The formula for esculating total cost including CMC charges shall be as under:

Total Cost for evaluation—

The formula for calculating total cost including CMC charges shall be as under:

That Cost for evaluation=

C+C**((A1/100)/(1.10^n)+(A2/100)/(1.10^n+1)+(A3/100)/(1.10^n+2)+(A4/100)/(1.10^n+3)+(A5/100)/(1.10^n+4)} and so on

C+C**(C+C**((A1/100)/(1.10^n)+(A2/100)/(1.10^n+1)+(A3/100)/(1.10^n+2)+(A4/100)/(1.10^n+3)+(A5/100)/(1.10^n+4)} and so on

C+C**((A1/100)/(1.10^n)+(A2/100)/(1.10^n+1)+(A3/100)/(1.10^n+2)+(A4/100)/(1.10^n+3)+(A5/100)/(1.10^n+4)} and so on

C+C**((A1/100)/(1.10^n)+(A2/100)/(1.10^n+1)+(A3/100)/(1.10^n+2)+(A4/100)/(1.10^n+3)+(A5/100)/(1.10^n+4)} and so

C+C**((A1/100)/(1.10^n)+(A2/100)/(1.10^n+1)+(A3/100)/(1.10^n+2)+(A4/100)/(1.10^n+3)+(A5/100)/(1.10^n+4)} and so

C+C**((A1/100)/(1.10^n)+(A2/100)/(1.10^n+3)+(A5/100)/(1.10^n+4)} and so

C+C**((A1/100)/(1.10^n)+(A2/100)/(1.10^n+3)+(A5/100)/(1.10^n+3)+(

applicable.

BACINIC charges offered for each subsequent year should be some or higher than preceding year.

BS.The CMC charges shall be offered within range of 3 to 10% of cost of equipment.

CMC charges are to be paid only later for each year during CMC period, applicable performs

9. Since CMC charges are to be paid only later for each year during CMC period, applicable performance guarantee amount after placement of contract shall be based on the cost of equipment excluding the cost of CMC Charges.

10. Performance bank quarantee applicable for CMC is to be submitted at start of the CMC and shall be applicable between 2.5% to 5% as specified in bid on total CMC Charges. The PBG submitted after award of contract shall be released only efter new PBG for the CMC period is submitted and accepted by buyer/consignee after due verification.Bank guarantee for CMC is to remain valid till completion of CMC period plus one year. The bank guarantee for CMC shall be submitted to buyer directly. In case, seller fall is to submit the PBG of does not provide services for the CMC contract effer explicy of veraring period then PBG of equipment shall be forfielded.

11. In case of splitting of order quantity, equipment cost and CMC charges (year to year) shall be matched individually.

12. The CMC Contract shall be an offline contract to be handled by buyer. The payment of CMC will be as per para 1 above.

General Clauses w.r.t RCM/FCM

rer RCM is applicable, for saliers (Regular QST registered selier who opted out of FCM as per notifications of QST like QTA . unregistered selier), Buyer have liability of paying the QST and QST cess to the governity of the property of th

2. For Registered sellers as par FCM, rates will be inclusive of prescribed race or use will be charged from buyer with invoice.

3. For Registered sellers who opted for RCM while quoting for specified category under section 9(3) like GTA rates will be exclusive of GST and GST cess as indicated by the buyer in Bability of buyer.

3. For Registered sellers who opted for RCM while quoting for specified category under section 9(3) like GTA rates will be exclusive of GST and GST cess as indicated by the buyer in the bld document will be the Bability of buyer. Unregistered sellers will invoice Series of GST and GST cess in Buyers cope. Seller will invoice Zero GST and GST cess in the Invoice to buyer.

Terms and Conditions

salve warranty shall include preventive maintenance inc stal completion of werranty period, Service personnel st sobles . Further there will be 98% uptime warranty durin e including calibration as per technical/ service /eperational m rel shell visit each consignee ette se recommended in the man furing warranty period on 24 (hrs) X 7 (days) X 365 (days) bas ufacturer, service charges and spares. During the warranty period commencing from dat ICBI/ service /operational manual, at least once in six manths, warranty shall not be includ

alls of pervice outlets in India to render services for equipment to be Pursished to buyer/consignees with complete address, telephone numbers, a mails att at time of making the supplies. It shall be the responsibilize that autherized service centres are smallship to exter to the areas where supplies are made within reasonable distance from where the service calls can be handled, betalls of toll free massless, for service call attraction of service requests also to be provided buyer/consignee at the time of supplies.

It shall be responsibility of seller to provide Docum mits regarding source of equipments such as copy of Performa invoice or any other documents to establish that the products supplied are menufactured by CBM ind

4. Packing and Marking: Medical equipments being very delicate and sensitive packing for the goods should be strong and durable enough to withestend transit including transhipment (if any), rough handling, open storage etc., without any demogis, deberioration etc. The also, weights and volumes of the packing cases, remotences of the final destination of the goods, evaluability or otherwise of transport and handling facilities at all points during transit up to final destination. Quality of packing, the manner of marking within and establish the packages and provision of accompanying documentation shall take in the casebleration the type of medical equipments being supplied. The accompanying documentation shall take in the casebleration of the packages shall be marked on three sides with indelible paint of proper quality; indicating contract number and date, brief description of goods including quantity, packing flat reference

S. Spare Parts:

ered that the required vignes before such disp.Me huyer/consignee before rsumables and spores for the c

meltie to carry out installation and commissioning, Supervision a no representatives for operating and maintaining the equipment line the installations, training and monusis the same shell also be and Demonstration of the goods. They shall provide required jigs and tools for assembly, minor civil works for the completion of the birits at and Supplying required number of operation and maintenance manual for the goods. In case the cotogory parameters are specifying an the maintaint sure that they furnish the list of equipments for carrying out reutine and preventive maintenence to buyer/consignee. They should make sure to periodically check the electrical sofety see nt. In case they de not have required equipment for such testing should ensure that the equipments checked for electrical sofety compliance through labs with facilities for such checking All software updates should be provided free of cost during warrenty period. 2. General Terms and Conditions act is governed by the <u>de</u> 2.1 This ex 3. Buyer Added Bid Specific Terms and Conditions rience Cartificate for the supply of the same to any Govt/ PSU/ any retion along with Supply/ Purchase Order. 2200 mcy is registered under MSME or MSIC, then END o or cortificate needs to be enclosed. 5.3 dealers:
OPTION (CLASSE: The Furcheer reserves the right to increase or decrease the quantity to be ordered up to 50 percent of bid quantity at the time of placement of or quantity by up to 50% of the contracted A quantity during the currency of the centract at the contracted rates. Bidders are bound to occupt the orders accordingly. 3.4 Buyer Added Bid Specific ATO Buyer Added text house ATC class

- 1. The Plasma sterilizer should be a fully microprocessor controlled unit with universal data acquisition system using state of the art Hydrogen peroxide gas plasma
- 2. The unit sho rid be free floor standing and mobile on lockable castors.
- 3. The regular and prolenged sterilization cycle time should be between 45 to 65minutes and a fast cycle which is around 35 minutes
- 4. The sterilization temperature should be around 55 degrees Celsius.
- 5. It should be able to sterilize all kinds of surgical instruments, hollow tubes, and endoscopes rigid as well as flexible.
 6. Should be able to sterilize flexible iumen with inside diameter of 1mm and length of 2000 mm & 500mm (rigid) respectively. The sterilization claims should be 5. Should be able to sterilize flexible iumen with inside diameter of 1mm and length of 2000 mm & 500mm (rigid) respectively. The sterilization becked by clinical testing.

 Should be able to sterilize single-through lumen PCD & hollow-type Trocar / cannula 2mm die, and length of 1500mm.

 The equipment should be to sterilize instruments of Robotic systems. (Claims backed by certificate from OEM of robotic system to be provided).

 All cycle related parameters should be displayed on a touch screen.

 All cycle related parameters should be made of stainless steel (AISI 316/304 grade)

 The unit should have a rectangular chamber withusable volume of 120 liters or more.

 The chamber should have two sliding shelves systems with competible SS instrument container (s) to be selected for 1 or 2 shelves.

 Door should be preferably vertically opening type.

 The concentration of Hydrogen Peroxide (H2O2) sterilant should be minimum pessible for safe and optimum sterilization items.

 Hydrogen peroxide (H2O2) sterilant should be either in closed cassette or cartridge ONLY for accurate dispensing.

 The unit should have no textic residues with primary bye products being water vapor and oxygen.

 The unit should have no textic residues with primary bye products being water vapor and oxygen.

 The unit should have an in-built thermal printer.

- 20. It should be equipped with facility for monitoring on nety
- 21. The operation of the sterilizer should have no requirement of additional water supply source22. The maintenance mode should be accessible from front screen for easy maintenance activity.
- 23. Electricity connection should be 220-240 V, AC at 50/60Hz and single pho
- 24. The plasma sterilizer should conform to the below mentioned norms and directives and certificates in support should be submitted.
 - ISO 9001:2008 Quality systems
 - ISO 13485:2003 Quality systems for medical devices
 - ISO 14937:2000 all requirements for sterilization of medical products
 - Direct93/42/EEC
- 25. The plasma sterilizer should confer to quality as per: Burepeen CE/USFDA /BIS/ equivalent approvals
 - EN 15014937

- 4 EN 15014837
 26. The unit should be supplied with
 1) Automatic heat sealing machine,
 2) Appropriate UPS to run at least one cycle backup,
 3) Starilization cartridges,
 4) Chemical Indicators,

 - B) Bi Indicators
 - 6) Bi incubator

 - a) mt measurer,b) Starffization traysc) Tyvek pouches for packing,

 - 9) Printer paper roll. 10) The complete co ble to run at least 100 cycles should be provided along with the system.

ed model as per specifications above should be installed and ensure satisfactory working.

ke	PE 4	work & Document details
A	aper	wing mandatory documents must be attached in the bid document as fied
	1011	ng which bid will be treated as" Non-Responsive"
	Cost CMC Tech	of spares, consumables and accessories not covered under werranty and ported shall be offered as percentage value of the system/unit in the hiral Bid ATC1/2
1		
2	Qec.	ments with regard to Details compliance etstement to be attached At Monel Dec
į	2(Re	quested in ATC)"
3	Deci	ments with report to Original Literature, Product catalogue , technical bleet from the firm/O.S.M with Highlighting as per the technical specification attach A "Additional Dec 2(Requised in ATC)"
4	Becu	conts with regard to list of Offering/Queted Items mentioning make, model (thy of each items must be "Additional Dec 4(Requested in ATE)"
		inty and Meintenance
- 1		inty for 5 years followed by CMC for 5 years including Spares & service for Items supplied
	in thi	particular tender including third-party Items and turnicey works .
	Mand	etery 2 PMs / Year with unlimited breakdown calls has to be attended by the
1	MENS	finantifacturer throughout the westenty & CMC period at alte.i.e. \$11048, \$MLLONS.
	Duly minici	igned Rundetory PM reports has to be submitted periodically, falling
_	will b	Initiated as per turm& condition of the tender.
T	Scop	of work

A Comment

NEIGRIHMS SHAPE OFFICER

The bidder has to mandatorily qualification

secffication & Scope of Work ,falling which bid will be treated as" Non-

The system is against buy back of one unit of plasmo steritizer make M/s Human Meditat, Model HATS 804 of 2011 and one ETO steritizer for which the declared reserve value is Re 748567.31 plus Rs 38006.00. The cost in price a-bid effords shall be inclusive of buy back veise. The buyback value of the system should size in indicated in the ATC decument bid as % of the total Cost of the system should size in and to the strate of the system should size in an extensive at Reserve value(ADV) for the record of the institute mandatorily and should cover the Minimum RDV of Rs 745567.31 Plus Rs 38080 approximates the strategy of the system should size of all accessories (respents, closed/ open etc) need to be clearly indicate in the technical bid Technical Bid ATCL/2 and will be consider for evaluation as in 800 or else bid will be treated as "one responsible". The CMC cost offered from 6th to the 19th year to be indicate in ATC ½ shell in indicate in percentage inclusive of GST and shall not axceed 5% of the system cost

1.5 Forms of END and PBB Successful Bidder can submit the Performance Security in the form of Account Payee Demand Oraft size (bealdes PBG which is allowed as par GaM GTC). DD abouid be made in favour of NEIGRIGMS EMD SECURITY shillding. After award of contract, Successful Bidder can upleed scanned copy of the DD in place of PBG and has to ensure delivery of hard copy to the original DB to the Buyer within 15 days of award of contract.

3.6 Parits of EMD and PSG.

8.6 Parits of EMD and PSG.

8.6 Parits on also submit the EMD with Payment online through RTGS / Internet benking in Beneficiary name NEIGRIMMS EMD SECURITY DEPOSIT

8.6 Parits of EMD and PSG.

8.6 HMS EMD SECURITY DEPOSITS Account No. 30270201

s of EMD and PBQ

stand in the same rous.

Bridge can submit the Performance Security in the form of Fixed Deposit Receipt also (besides PSG which is allowed as per GeN GTC), FDR should be made out or pledged in the name of NEIGRIMMS END SECURITY DEPOSITS and of the Seller). The benic should certify on it than the deposit can be withdrawn only on the demand or with the senedan of the pledgee. Per release of Security Deposit, the FDR will be released in favour of bidder by the Buyer making endorsement on the back of the FDR duly signed and stamped along with covering letter. Successful Bidder has to uplead scanned copy of the FDR document in place of PBG and has to ensure delivery of hard copy of

3.8 Authorised Service Centre within the state of Odisha, along with a dedicated contact po

3.8 Inspection: Nominated Inspection ins Pro-dispatch ins Post Receipt ins milisted inspection Agency: On behalf of the Buyer organization, any one of the following inspection Agency would be conducting inspection-dispetch inspection at Solier Pramises (applicable only if pre-dispetch inspection clause has been selected in ATC)38M and QC certification at Receipt inspection at consignee site before acceptance of stores:NBIGRBHNS CT Project Monitoring unit

3,16 Generi After sward sward of co error and of contract - Successful Sidder shall have to get Detailed Design Drawings approved from buyer before starting inbrication, Successful Sidder shall submit Detailed Design Drawings for Suyer's approved contract. Suyer shall, either approve the drawings or will provide complete list of modification required in the drawings within 7 days, Seller shall be required to ensure supply as per approved Drawing. Some supply as per approved Drawing. When the delivery period shall be refined without LD for the period of delay in approved of Drawing.

3.11 Cortific

int, ATC and Corrie

3.13 Cortificates: The bidder is required to unle

2.14 CortNicates:
To be eligible for award of contract, Bidder / OEM must possess foliobuy beack basis to offer disposal value in ATC documents. MP/ FDA: F No. HENSR/ S&P/ 0-16/2020-21 on

3.15 Purchase Preference (Centre): Indian suppliers of this Item are not (d) of Public Procurement (Preferen reference (Lancey). The service of this flow are not billowed to participate and/ or campete in procurement by some foreign governments. Bidders / pr Yocurement (Preference to Make in India) Order, 2017

3.16 Purchase Preference (Central):

Procurement under this bid is reserved for purchase from Micro and Small Enterprises whose credentists are validated online through Udyeg Aedhear for that product estagety. If the bidder wonts to avail the reservation benefit, the
Midder must be the manufacturer of the offered product in case of bid for supply of goods. Traders are excluded from the purview of Public Procurement Policy for Micro and Small Enterprises. In respect of bid for Service 1, the bidder must be the Service provider of the offered Service. Selevent documentary evidence in this regard shall be upleaded along with the bid in respect of the offered product or service.

3.17 Scippe of Supply: Scope of supply (Bid price to include all cost compone

3.16 Turnover: Bidder Turn Over Criteria: The min

Bilder furn Over Criteria: The minimum average annuel financial tursover of the bilder during the last three years, ending on 31st March of the previous financial year, should be as indicated in the bild document. Decum entary evidency in the form of certified Audited Balance Sheets of relevant periods or a certificate from the Chartered Accountant indicating the turnover details for the relevant period shall be upleaded with the bild. In the bild of constitution of the bilder is less than 3 year old, the average turnover in respect of the completed financial years after the debt of constitution shall be taken into account for this criteria.

2.15 Turnevers
OBM Then Over Criteries The minimum average annual financial turnever of the OBM of the effered product during the last three years, ending an 31st March of the previous financial year, should be as indicated in Decumptory evidence in the form of certified Audited Balance Shouts of relevant periods or a certificate from the Chartered Accountant / Cost Accountant Indicating the turnever details for the relevant period of the bid. In case the date of constitution (Incorporation of the OBM is less than 3 year and, the overage and, the correspond of the constitution (Incorporation of the OBM is less than 3 year and, the overage of the completed financial years after the date of constitution shall be taken into account under this criterion. half be oploaded with it for this criteria, in

3.20 Generic: Bidders phasi quete only those products is the bid t ill not be declared end-of-life by the OEM before this period.

is live advised to check applicable GST on their own before quoting. Buyor will not to hum of quoted GST %.

rever Bidders are insisting for End User Certific

23 Generic: its Sheet of the product(s) offered in the bid, are to be upi trameters, the bid is liable for rejection.

3.24 Seriaric:

Experience Criteria: The Bidder or its ORM (themselves or through resolves)) should have requirely, manufactured and supplied same or similar Category Products to any Central / State Govt Organization / PSU / P
Company for 8 years before the bid opening date. Copies of relevant contracts to be submitted along with bid in support of having supplied some quantity suring each of the year. In case of bunch bids, the primary
legislative value should meet this criterion.

ition/ handling/ storage/ safety/ health/ environment a written/ printed/ pasted on the body of the packing

3,26 Generic: Installation, Co

3.27 Generic

3.28 Generic: Shalf Life: The

3.29 Ge

3.29 Generic: Upload Namufacturer authorization to be furnished along with the bid.

3.30 Generic:

3.39 dendric:

1. The Seler shall not assign the Contract in whole or part

2. The Seler shall not sub-contract the Contract in whole or

3. The Seler shall, notwithstanding the consent and assign

Contract and the Selers obligations there under.

part without obtaining the prior written consent of buyer, rie or part to any entity without obtaining the prior written conse algoment/sub-contract, remain jointly and severally liable and n

3.31 Generalist
The successful initialization and commissioning of the goods supplied for the successful installation and commissioning of the goods supplied part of supply and cost should be included in bid price: Supply transport, leading ,unloading, all related d services , associated accessories/ or reliewing acc retion and training stry practice, fo

3.32 Suyer Added Bid Specific ATQ Suyer upleaded ATC document <u>Click here to vises the file</u>.

Adn Die Procuren digerrys shilleng-18





GEM/2022/B/1921525-C5

Following terms and conditions supersede all existing "Buyer added Bid Specific Terms and conditions" given in the

Buyer Added Bid Specific Additional Terms and Conditions

- 1. Experience Certificate for the supply of the same to any Govt/ PSU/ any renowned private organisation along
- 2. If the agency is registered under MSME or NSIC, then EMD exemption certificate needs to be enclosed.
- 3. OPTION CLAUSE: The Purchaser reserves the right to increase or decrease the quantity to be ordered up to 50 up to 50% of the contracted A quantity during the currency of the contract at the contracted rates. Bidders ar

4. Buyer Added text based ATC clauses

Low Temperature Hydrogen Peroxide Gas sterilizer

- 1. The Plasma sterilizer should be a fully microprocessor controlled unit with universal data
- 2. The unit should be free floor standing and mobile on lockable castors.
- 3. The regular and prolonged sterilization cycle time should be between 45 to 65minutes at
- 4. The sterilization temperature should be around 55 degrees Celsius.
 - 5. It should be able to sterilize all kinds of surgical instruments, hollow tubes, and endos
- 6. Should be able to sterilize flexible lumen with inside diameter of 1mm and length of 2 7. Should be able to sterilize single-through lumen PCD & hollow-type Trocar / cannula 2mm
- 8. The equipment should be to sterilize instruments of Robotic systems. (Claims backed by c

9. All cycle related parameters should be displayed on a touch screen.

- 10. Sterilization chamber should be made of stainless steel (AISI 316/304 grade)
- 11. The unit should have a rectangular chamber withusable volume of 120 liters or more.
- 12. The chamber should have two sliding shelves systems with compatible SS instrument co

13. Door should be preferably vertically opening type.

- 14. The concentration of Hydrogen Peroxide (H2O2) sterilant should be minimum possible fo 15. Hydrogen peroxide (H2O2) sterilant should be either in closed cassette or cartridge ONL
- 16. The unit should have no toxic residues with primary bye products being water vapor and 17. The unit should automatically monitor all its operations with audiovisual alarmsincluding
- 18. All sterilization data should be stored in SD memory card.

19. It should have an in-built thermal printer.

- 20. It should be equipped with facility for monitoring on network computer
- 21. The operation of the sterilizer should have no requirement of additional water supply sou
- 22. The maintenance mode should be accessible from front screen for easy maintenance act
- 23. Electricity connection should be 220-240 V, AC at 50/60Hz and single phase.
- 24. The plasma sterilizer should conform to thebelow mentioned norms and directives and c

- ISO 9001:2008 - Quality systems

- ISO 13485:2003 - Quality systems for medical devices

- ISO 14937;2000 - all requirements for sterilization of medical products

- Direct93/42/EEC
- 25. The plasma sterilizer should confer to quality as per:
 - European CE/USFDA /BIS/ equivalent approvals
 - EN ISO14937
- 26. The unit should be supplied with
 - 1) Automatic heat sealing machine,
 - 2) Appropriate UPS to run at least one cycle backup,
 - 3) Sterilization cartridges,
 - 4) Chemical indicators,
 - 5) BI indicators,
 - 6) BI incubator,
 - 7) Sterilization trays
 - 8) Tyvek pouches for packing,
 - 9) Printer paper roll.
- 10) The complete consumable to run at least 100 cycles should be provided along wi

The quoted model as per specifications above should be installed and ensure satisfactory wor

	A Following mandatory documents must be attached in the bid document as specified						
	,failing which bid will be treated as" Non-Responsive"						
	Cost of spares, consumables and accessories not covered under warranty and CMC period shall be offered as percentage value of the system/Unit in the Technical Bid ATC1/2						
;	1						
:	Documents with regard to Details compliance statement to be attached At "Additional Doc 2(Requested in ATC)"						
-	Documents with regard to Original Literature, Product catalogue ,Technical datasheet from the firm/O.E.M with Highlighting as per the technical specification must attach At "Additional Doc 3(Requested in ATC)"						
4	Documents with regard to list of Offering/Quoted items mentioning make, model & quantity of each items must be "Additional Doc 4(Requested in ATC)"						
8	Warranty and Maintenance						
1	Warranty for 5 years followed by CMC for 5 years including Spares & service for all the items supplied						
	in this particular tender including third-party items and turnkey works .						
2	Mandatory 2 PMs / Year with unlimited breakdown calls has to be attended by the						
۲	Bidder/manufacturer throughout the warranty & CMC period at site.i.e. NEIGRIHMS, SHILLONG.						
3	Duly signed Mandatory PM reports has to be submitted periodically, falling which necessary action						
	will be initiated as per term& condition of the tender.						
Ī	Scope of work						

M.

Horse . The

kep/re

- 1 The bidder has to mandatorily quote for all the items /stores mentioned in the Technical
 - Specification & Scope of Work ,failing which bid will be treated as" Non-Responsive"
- The system is against buy back of one unit of plasma sterilizer make M/s Human Meditek, Model HMTS 80L of 2011 and one ETO sterilizer for which the declared reserve value is Rs 745567.31 plus Rs 30000.00. The cost in price e-bid offered shall be inclusive of buy back value. The buyback value of the system should also be indicated in the ATC document bid as % of the total Cost of the system in order to arrive at Reserve value(RDV) for the record of the Institute mandatorily and should cover the Minimum RDV of Rs 745567.31 Plus Rs 30000 approx. Prices of all accessories (reagents, closed/ open etc) need to be clearly indicated as % of the total price in the technical bid Technical Bid ATC1/2 and will be consider for evaluation as in BOQ or else bid will be treated as "non responsive". The CMC cost offered from 6th to the 10th year to be indicate in ATC ½ shall in Indicate in percentage inclusive of GST and shall not exceed 5% of the system cost.
- 5. Successful Bidder can submit the Performance Security in the form of Account Payee Demand Draft also (bes After award of contract, Successful Bidder can upload scanned copy of the DD in place of PBG and has to ensure
- 6. Bidders can also submit the EMD with Payment online through RTGS / internet banking in Beneficiary name Naddress MAWDIANGDIANG, SHILLONG-793018, MEGHALAYA.
 - Bidder to indicate bid number and name of bidding entity in the transaction details field at the time of on-line Successful Bidder can submit the Performance Security in the form of Fixed Deposit Receipt also (besides PBC of the Seller). The bank should certify on it that the deposit can be withdrawn only on the demand or with the endorsement on the back of the FDR duly signed and stamped along with covering letter. Successful Bidder h within 15 days of award of contract.
- 8. Authorised Service Centre within the state of Odisha, along with a dedicated contact person with telephone n
- 9. **Nominated Inspection Agency:** On behalf of the Buyer organization, any one of the following Inspection Agency: Or behalf of the Buyer organization, any one of the following Inspection Agency: Or Pre-dispatch Inspection at Seller Premises (applicable only if pre-dispatch inspection clause has been selected Post Receipt Inspection at consignee site before acceptance of stores: NEIGRIHMS OT Project Monitoring unit
- 10. After award of contract Successful Bidder shall have to get Detailed Design Drawings approved from buyer I contract. Buyer shall, either approve the drawings or will provide complete list of modification required in the Buyer. If there is delay from buyer side in approval of drawing- the delivery period shall be refixed without LE
- 11. Bidder's offer is liable to be rejected if they don't upload any of the certificates / documents sought in the Bid
- 12. Material Test Certificate Should Be Sent Along with The Supply. The Material Will Be Checked by Buyer's Lab
- 13. The bidder is required to upload, along with the bid, all relevant certificates such as BIS licence, type test cert
- 14. To be eligible for award of contract, Bidder / OEM must possess following Certificates / Test Reports on the da basis to offer disposal value in ATC documents.
- 15. Indian suppliers of this item are not allowed to participate and/ or compete in procurement by some foreign g
 Procurement (Preference to Make in India) Order, 2017
- 16. Procurement under this bid is reserved for purchase from Micro and Small Enterprises whose credentials are the manufacturer of the offered product in case of bid for supply of goods. Traders are excluded from the purthe offered Service. Relevant documentary evidence in this regard shall be uploaded along with the bid in res
- 17. Scope of supply (Bid price to include all cost components): Supply Installation Testing Commissioning of Goo
- 18. Bidder Turn Over Criteria: The minimum average annual financial turnover of the bidder during the last three of certified Audited Balance Sheets of relevant periods or a certificate from the Chartered Accountant / Cost A incorporation of the bidder is less than 3 year old, the average turnover in respect of the completed financial
- 19. ØEM Turn Over Criteria: The minimum average annual financial turnover of the OEM of the offered product due vidence in the form of certified Audited Balance Sheets of relevant periods or a certificate from the Chartere donstitution / incorporation of the OEM is less than 3 year old, the average turnover in respect of the complet RELATED TO primary product having highest bid value should meet this criterion.
- 20. Bidders shall quote only those products in the bid which are not obsolete in the market and has at least 7 year
- 21. Bidders are advised to check applicable GST on their own before quoting. Buyer will not take any responsibilit quoted GST %.
- 22. End User Certificate: Wherever Bidders are insisting for End User Certificate from the Buyer, same shall be

23. Data Sheet of the product(s) offered in the bid, are to be uploaded along with the bid documents. Boyers can the bid is liable for rejection.

Scorgo

afich

Store & Procurement Officer

MEIGRIHMS Shillong 18

- 24. Experience Criteria: The Bidder or its OEM {themselves or through reseller(s)} should have regularly, manufa before the bid opening date. Copies of relevant contracts to be submitted along with bid in support of having criterion.
- 25. For hazardous chemical/item, all precautionary measure as per regulation from the point of transportation/ hamself Batch No./ date of manufacturing/ Gross Weight/ Net Weight/ shelf Life etc are to be written/ printed/ printe
- 26. Installation, Commissioning, Testing, Configuration, Training (if any which ever is applicable as per scope of
- 27. Products supplied shall be nontoxic and harmless to health. In the case of toxic materials, Material Safety Dat
- 28. Shelf Life: The Product to be supplied must have minimum consumables 12 months Shelf Life Shelf Life. On
- 29. **Upload Manufacturer authorization:** Wherever Authorised Distributors are submitting the bid, Manufacture furnished along with the bid.
- 30. 1. The Seller shall not assign the Contract in whole or part without obtaining the prior written consent of buye 2. The Seller shall not sub-contract the Contract in whole or part to any entity without obtaining the prior writ 3. The Seller shall, notwithstanding the consent and assignment/sub-contract, remain jointly and severally lia Sellers obligations there under.
- 31. The successful bidder has to supply all essential accessories required for the successful installation and comn supply and cost should be included in bid price: Supply transport, loading ,unloading, all related d services , a
- 32. Buyer uploaded ATC document Click here to view the file.

Disclaimer

The additional terms and conditions have been incorporated by the Buyer after approval of the Competent Authority consequences thereof including any eccentricity / restriction arising in the bidding process due to these ATCs and dudemanding Tender Sample, incorporating any clause against the MSME policy and Preference to make in India Policy governed by OM of Department of Expenditure shall be null and void and would not be considered part of bid. Further

*This document shall overwrite all previous versions of Bid Specific Additional Terms and Conditions.

This Bid is also governed by the General Terms and Conditions

A.

Acous

Lylm 20

Ref